

Robust, extended-cuff hand protection for food processing and heavy-duty jobs

- **Strong protection:** TouchNTuff® 92-665 nitrile gloves reliably protect in the event of accidental exposure to chemicals
- **Comfort and durability:** The soft yet tough nitrile offers a comfortable feel while resisting rips and tears
- **Longer length:** An extended cuff enhances protection over the wrist and forearm
- **Secure grip:** Textured fingertips help wearers confidently grip objects and tools
- **Ideal for food applications:** These gloves are compliant with food handling requirements



Industries

- Life Sciences
- Chemical
- Food Processing

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Handling incoming goods
- Maintenance
- All food processing, applications that have food contact

TECHNICAL DATA SHEET

| Product Information | |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| External Glove Surface | Textured Fingers |
| Audit Standards | ISO 9001 |
| Packaging Overview | 100 gloves per dispenser 10 dispensers per case 1000 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Thailand |
| Product Segmentation | High Risk |
| Antistatic | Yes EN1149 |
| Vulcanization Chemical Accelerators | <ul style="list-style-type: none"> Zinc Dibutyldithiocarbamate (ZDBC) <p><i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i></p> |

PHYSICAL PROPERTIES

| | Typical Values | | Testing Method |
|-----------------------------------------|---------------------|--------------------|---------------------|
| Length (mm/inches) | 300 / 12 | | ASTM D3767,EN 420 |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils) | 0.11 / 4.3 | | ASTM D3767,EN 420 |
| Finger Thickness (mm/mils) | 0.14 / 5.5 | | ASTM D3767,EN 420 |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | ≥ 14 | ≥ 14 | ASTM D412 & D573 |
| Elongation at Break (%) | ≥ 500 | ≥ 400 | ASTM D412 |
| Force at break (N) | ≥ 6 | ≥ 6 | EN 455-2 |

ORDERING INFORMATION

| Size | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|-------------|-------------|---------------|
| Product Code | 92665080 | 92665090 | 92665100 |

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

BR +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

